

ODE-3-340140-304A

Optidrive E3 VFD Datasheet

5,5 kW (7,5 HP), 14 A, 380-480 V, 3PH

Variadores de frecuencia



Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	17,2 A
Supply Fuse or MCB (Type B)	25 A

Output Ratings

Motor Output Rating	5,5 kW (7,5 HP)
Output Voltage	0 – Supply Voltage
Output Current	14 A

Cable Information

Max Supply Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Size	8 mm ² (0,01 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	Sin filtro CEM interno
Brake Transistor	Transistor de freno interno
Enclosure	IP66 Exterior no conmutado
Display	
PCB Coating	


Dimensions

Size	3
Height	310 mm (12,2 in)
Width	211 mm (8,31 in)
Depth	225 mm (8,86 in)
Weight	6,6 kg (14,55 lbs)
Fixings	4 x M4

Packaged Dimensions

Height	305 mm (12,01 in)
Width	270 mm (10,63 in)
Depth	440 mm (17,32 in)
Weight	7,6 kg (16,76 lbs)



 **Buy this drive or get more information**
Find your local sales partner on
inverterkdrives.com

