

# ODV-3-240095-3F12-MN

Optidrive Eco VFD Datasheet

**4 kW (5 HP), 9,5 A, 380-480 V, 3PH**

Variadores de frecuencia con filtro CEM y  
Pantalla TFT Pantalla



## Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	8,6 A
Supply Fuse or MCB (Type B)	10 A

## Output Ratings

Motor Output Rating	4 kW (5 HP)
Output Voltage	0 – Supply Voltage
Output Current	9,5 A

## Cable Information

Max Supply Cable Size	8 mm <sup>2</sup> (0,01 sq in)
Max Motor Cable Size	8 mm <sup>2</sup> (0,01 sq in)
Max Motor Cable Length	100 m (328 ft)

## Factory Build Options

EMC Filter	CEM interno
Brake Transistor	Sin transistor de freno
Enclosure	IP20
Display	Pantalla TFT
PCB Coating	Estándar

## Dimensions

Size	2
Height	221 mm (8,7 in)
Width	110 mm (4,33 in)
Depth	185 mm (7,28 in)
Weight	1,8 kg (3,97 lbs)
Fixings	4 x M4

## Packaged Dimensions

Height	265 mm (10,43 in)
Width	145 mm (5,71 in)
Depth	230 mm (9,06 in)
Weight	1,9 kg (4,19 lbs)



 **Buy this drive or get more information**  
Find your local sales partner on  
[invertekdrives.com](http://invertekdrives.com)

